

Stepp STPH Patch bodies have triple wall construction, inner hopper constructed of 10 gauge material. Oil jacketed chamber to be constructed of 12 gauge material insulated with 2" of 1½# density hi-temperature fiberglass insulation. Heat risers are designed into the hopper to help evenly distribute heat into the center of material. Insulation cover to be 16 gauge. Shall be mounted to the truck chassis with a spring loaded slip saddle mount.

Available Sizes...

- 4.0 Cubic Yards
- 5.0 Cubic Yards
- 6.0 Cubic Yards
- 7.0 Cubic Yards

Design Benefits...

- Triple Wall Construction
- Top Loading Doors Controlled from rear
- Auger Delivery
- 490,000 BTU Beckett Diesel Burners
- Auto Temp Controls
- Full Hydraulic System

Options...

- Gravity Tack Tank
- Tack Tank with Pumping System
- Overnight Heat
- Spoils Bin
- Wash Down System
- · Lighting packages, Safety Lighting, Arrow Board, Tool holders







Quick Spec	STPH 4.0	STPH 5.0	STPH 7.0
Capacity	4.0 Cubic Yard 5 Ton	5.0 Cubic Yard 6 Ton	7.0 Cubic Yard 9 Ton
Dimensions (LxWxH)	96"x 71"x 40"	120"x 71"x 40"	120"x 71"x 51"
Loading Height	100"	100"	111"
Diesel Burner BTU	490,000 BTU	490,000 BTU	490,000 BTU
Heat Transfer Oil Capacity	160 Gallon	190 Gallon	225 Gallon