



**EXTREME DRIFTS. INSANE DEADLINES.  
PLOW THROUGH IT ALL.**



## PLOW ATTACHMENTS

Whether you're up against deep snow drifts or thick ice buildup, Oshkosh® Snow Plow Attachments help you clear the runway efficiently and effectively. With a variety of hard-hitting plow configurations and blade lengths to choose from, you can take on the worst conditions with confidence and control.

**TAKE BACK THE RUNWAY.**

### PERFORMANCE FEATURES

#### Heavy-Duty Plow Construction

- Dual caster wheels with 360-degree rotation, on 18 ft. (5.5 m) and larger plows
- Single caster wheels with 360-degree rotation, on 14 ft. (4.3 m) and 16 ft. (4.9 m) plows
- 50 in. (1270 mm) moldboard with rubber cushioned design
- Available for "J" hook, straight pin, Hustings, DIN and hands-free DIN hitches
- Deep radius design for more efficient snow movement –utilizes vehicle's kinetic energy to increase snow displacement
- Available rollover solid steel design

#### Smart Design

- Oshkosh® proven design since 2005
- Blade lengths of 14, 16, 18, 20, 22 and 24 ft. (4.3, 4.9, 5.5, 6.1, 6.7 and 7.3 m)
- Cutting edges available in steel, carbide, polyurethane, rubber or rubber with carbide insert
- Bright yellow moldboard with high visibility for safety
- Configured to fit each airport's unique requirements



# EVER DURABLE. ALWAYS CAPABLE. OSHKOSH SNOW PLOW ATTACHMENTS.



## PLOW OPTIONS

### Straight Plow:

- 50 in. (1,270 mm) moldboard height
- 50 in. (1,270 mm) discharge height
- 3/8 in. (9.5 mm) HMW polyurethane thickness with 3/16 in. (4.8 mm) steel backing plate
- Cutting edge angle of 65, 75 and 85 degrees
- 14, 16, 18, 20, 22 and 24 ft. blade lengths (4.3, 4.9, 5.5, 6.1, 6.7 and 7.3 m)
- Steel, carbide, polyurethane and rubber cutting edges
- “J” hook, straight pin, Hustings, DIN and hands-free DIN hitches

### Flared Plow:

- 50 in. (1,270 mm) moldboard height
- 64 in. to 76 in. (1,626 mm to 1,930 mm) discharge height
- 3/8 in. (9.5 mm) HMW polyurethane thickness with 3/16 in. (4.8 mm) steel backing plate
- Cutting edge angle of 65, 75 and 85 degrees
- 18, 20, 22 and 24 ft. blade lengths (5.5, 6.1, 6.7 and 7.3 m)
- Steel, carbide, polyurethane and rubber cutting edges
- “J” hook, straight pin, Hustings, DIN and hands-free DIN hitches

### Roll Over Plow:

- 82 in. (2,083 mm) discharge height
- 10 gauge steel moldboard
- Entire plow rotates 180 degrees to cast snow left or right
- 12 ft. (3.7 m) blade length
- 10 ft. (3.0 m) plow path
- Steel cutting edge
- Carbide skid shoes
- 10 in. (254 mm) steel caster wheels
- Integral rollover type hitch

### 3 Function Under Body Cutting/Scraping Blade:

- 12 ft. (3.7 m) long steel or polyurethane cutting blade
- Lift, swing and curl functions
- 2 function option for lift and swing only available
- Excellent option to help remove ice from a runway

**OSHKOSH**  
AIRPORT  
PRODUCTS

**PLOW  
ATTACHMENTS**

[oshkoshairport.com](http://oshkoshairport.com)

+1 920 235 9151